

## STYLE P50 / P40T SPEAKER SYSTEMS

### OPERATIONAL PRINCIPLES

One way loudspeaker  
360° uniform sound dispersion  
Extremely broad frequency bandwidth

### DISTINCTIVE FEATURES

Elegant design, variable colours  
Hung from ceiling, minimum 9,84ft ceiling height  
Concealed connections  
Superior tone quality  
Excellent voice clarity characteristics

### APPLICATIONS

Excellent sound quality for all requirements  
Ranging from soft background music up to the reproduction of high level stereo in surround and HiFi quality

### SUITABILITY

Sound redefines the perception of space.

Quality acoustics influences our well-being and may extend the time we spend in shops, bars, restaurants and customer orientated locations or in the wellness areas.

The conical geometry of the P50 produces a uniform dispersion of sound, but conceals its source. A soft comfortable sound fingerprint is created through the use of a novel aluminium membrane. Maximum sound quality is achieved regardless of the room's size, be it large or small. The elegant form is especially suited for representative locations such as foyers and festival halls with high ceilings.


Contrary to conventional speakers, a considerably higher level of quality sound with less sound equipment is achieved. Each model is available in three distinct technical versions with a minimum difference in appearance.

This design orientated concept of construction offers variety from pure sound to attractive coexistence with different light systems. This additional flexibility means that the unit can be readily adapted to changing room aspects without having to replace the underlying model.



### SWITCHING UNIT

TR-20  
Code 31011



### TECHNICAL DATA

	STYLE P50	STYLE P40T
TYPE	Suspending mounted	Suspending mounted
PRINCIPLE	One way	One way
ENCLOSURE	High-performance plastic flange 150° continuous use / Recyclable / Formstable up to 220° / Fireclass UL94 / V-0 self extinguish	High-performance plastic flange 150° continuous use / Recyclable / Formstable up to 220° / Fireclass UL94 / V-0 self extinguish
COLOUR	White RAL 9010	White RAL 9010
DRIVER EQUIPMENT	-----	100V transformer
IMPEDANCE	16 Ohm	-----
NOMINAL PWR / MUSIC	50W RMS / 90W	40/20/10/5W RMS
SENSITIVITY (1W @1m, 2,83V @1m)	83,4dB @16Ohm	83,4dB
MAX. SPL	100dB	100dB
FREQUENCY RESPONSE	105-20.000 Hz (+/- 3dB)	105-20.000 Hz (+/- 3dB)
CONNECTORS	Screw terminal	Screw terminal
NET WEIGHT	2,68 lb	3,57 lb
TRANSPORT WEIGHT	3,43 lb	4,32 lb

### DIMENSIONS

